

**IMPLEMENTATION OF ADAPTIVE FILTERS BASED
ON NEURAL NETWORKS FOR DIGITAL SIGNAL PROCESSING**

Stepuro O.V.

e-mail: oleksandra.stepuro@nure.ua

Scientific supervisor – sn. I. Chumak V.S.

Kharkiv National University of Radioelectronics, Department of MTS
Kharkiv, Ukraine

One approach that overcomes the limitations of traditional methods is the use of multi-layer neural network architectures such as MLP and RNN. These networks can automatically learn from input signals and adjust their parameters for optimal filtering. The network consists of three main components: an input layer, one or more hidden layers, and an output layer, which allows for nonlinear transformation of the signal. The network is trained using the backpropagation algorithm, which minimizes the error between the actual and desired output.

Adaptive filters are essential tools for reducing noise and interference in digital signals. Traditional adaptation methods, such as the Least Mean Squares (LMS) and Recursive Least Squares (RLS) algorithms, work well for linear signals, but their effectiveness decreases when processing nonlinear or complex data. This limitation arises because these methods cannot account for complex relationships between signals and noise that are often present in real-world applications. To address this issue, neural networks, particularly multi-layer perceptrons (MLP) and recurrent neural networks (RNN), are increasingly used, as they can adapt to varying signal conditions and effectively handle nonlinear, high-dimensional data.

The filtering process in a neural network adaptive filter involves passing the input signal through several layers of the network, with each layer responsible for a certain level of data abstraction. After each training iteration, the weights of the neurons are adjusted to minimize the error between the desired result and the actual output. This enables the filter to adapt to changes in signal characteristics such as frequency spectrum or noise level. The mathematical description of a neural network adaptive filter can be expressed by the error function E , which the network attempts to minimize during the training process:

$$E = \frac{1}{2} \sum_{t=1}^T (d(t) - y(t))^2$$

where E is the error function, $d(t)$ is the desired signal (e.g., a noise-free signal), $y(t)$ is the output signal after filtering, and T is the number of time samples.

The backpropagation algorithm is used to adjust the network's weights, which allows for optimal filtering results. This approach has advantages over

traditional methods in situations where the signal is nonlinear or has complex statistical characteristics that are difficult to describe using classical algorithms.

Due to the ability of neural networks to effectively process large volumes of data and adapt to changes in input signals, they are used for signal filtering in real-world applications such as biomedical signal processing (EEG, ECG), audio and video signals, and telecommunications to reduce noise and distortion [1-4].

The use of neural network filters in biomedical signal processing is particularly relevant, as these signals exhibit high variability and are often accompanied by various types of noise. In these cases, classical filters often cannot provide sufficiently accurate filtering, while neural networks, due to their adaptability, provide much better results. Similarly, in telecommunications, neural networks can significantly improve signal quality under low signal levels or high noise conditions.

The adaptability of neural network filters also makes them effective in situations where signal characteristics change, such as in mobile communications, where the signal level constantly varies depending on the distance to the transmitter or obstacles in the signal path.

Therefore, neural networks for implementing adaptive filters are a powerful tool for digital signal processing, enabling effective handling of nonlinear and complex data while reducing the impact of noise and interference on signal quality.

List of sources used:

1. Чумак В.С. Використання нейронних мереж в адаптивних системах онлайн-медичної освіти на базі мікроконтролерів STM32 в умовах воєнних криз // Автоматизація, електроніка та робототехніка. Стратегії розвитку та інноваційні технології (AERT-2023): матеріали V форуму, 29–30 листопада 2023 р. – Харків: ХНУРЕ, 2023. – С. 134-135.

2. V.Semenets, V. Chumak, I. Svyd, O. Zubkov, O. Vorgul, N.a Boiko. Designing the Structure of a General-Purpose Telemedicine Complex. International Scientific and Practical Conference Theoretical and Applied Aspects of Device Development on Microcontrollers and FPGAs (MC&FPGA). Kharkiv. Ukraine. 2021, pp. 47-48, doi: 10.35598/mcfpga.2021.016.

3. Чумак, В. С., Аврунін, О. Г., Чугуй, Є. А., & Свид, І. В. (2021). Аналіз принципів побудови телемедичних комплексів широкого призначення. АСУ та прилади автоматики, 177, 80–85.

4. Малахова О. Ю. Електроміограф на FPGA / О. Ю. Малахова, І.О. Шевцов // Авіація, промисловість, суспільство : матеріали III Міжнар. наук.-практ. конф. (м. Кременчук, 12 трав. 2022 р.) / МВС України, Харків. нац. ун-т внутр. справ, Кременчуц. льотний коледж., Наук.парк «Наука та безпека». – Харків : ХНУВС, 2022. – С. 117 -120.